

Daylight 400

Technical data

Technical features

| | |
|--|-------------------------|
| Dimensions | 19 cm x 16.5 cm x 18 cm |
| Weight | 1.6 kg (3.53 lbs) |
| Lamp: | |
| HQI -TS 70/D UVS EXCELLENCE (Osram) | 5600 K (UV free) |
| or | 3200 K (UV free) |
| HQI -TS 70/WDL UVS EXCELLENCE (Osram) | |
| Electronic ballast | integrated |
| Watt (consumption) | 70 W |
| Watt (output equivalent to tungsten) | 400 W |
| Lamp life | |
| HQI -TS 70/D UVS EXCELLENCE | 12000 h |
| HQI -TS 70/WDL UVS EXCELLENCE | 12000 h |
| Fresnel lens | 120 mm |
| Colour temperature | 5600 K or 3200 K |
| Voltage AC | 220 V - 240 V |
| Light beam | 10° - 56° |
| Frequency (input) | 50/60 Hz |
| Frequency (output) | 165 Hz |
| Compliance | CE |

Photometric data

| | |
|--------------------|--------|
| Lux at 1 m (spot) | 18,000 |
| Lux at 1 m (flood) | 2400 |
| Lux at 2 m (spot) | 4500 |
| Lux at 2 m (flood) | 600 |
| Lux at 3 m (spot) | 2500 |
| Lux at 3 m (flood) | 300 |